

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



537 952

(43) International Publication Date
1 July 2004 (01.07.2004)


PCT

(10) International Publication Number
WO 2004/055599 A1

- (51) International Patent Classification⁷: G03F 9/00, 7/20, H01L 23/544, G01R 31/316
- (21) International Application Number:
PCT/IB2003/005645
- (22) International Filing Date: 4 December 2003 (04.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/433,311 13 December 2002 (13.12.2002) US
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (74) Common Representative: KONINKLIJKE PHILIPS ELECTRONICS N.V.; c/o Waxler, Aaron, P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): AMATO, Joseph, M. [US/US]; P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).
- Declaration under Rule 4.17:
— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES,

[Continued on next page]

(54) Title: RESISTOR STRUCTURES TO ELECTRICALLY MEASURE UNIDIRECTIONAL MISALIGNMENT OF STITCHED MASKS



(57) Abstract: An apparatus and method for matched variable resistor structures to electrically measure unidirectional misalignment of stitched masks for etched interconnect layers includes a first test pad (101) and a second test pad (102) for measuring resistance therebetween; a first resistive element (105) electrically connected at a first end to the first test pad (101); and, a second resistive element (110) electrically connected at a first end to the second test pad (102). The first resistive element and the second resistive element are electrically connected by a vertical offset (112). The resistance measured between the first test pad and the second test pad is variable in accordance with an alignment of the first resistive element and the second resistive element relative to the vertical offset, see Fig. 1C-E. An indicator may optionally provide an indication that the resistive elements are in alignment.

WO 2004/055599 A1